

# TECHNICAL SPECIFICATIONS

## GA 5-7-11

COMPRESSOR TYPE		Working pressure WorkPlace		Capacity FAD* min-max			Installed motor power		Noise level**	Weight (kg)			
										WorkPlace		WorkPlace Full Feature	
		bar(e)	psig	l/s	m³/h	cfm	kW	hp		dB(A)	Floor-mounted	Tank-mounted	Floor-mounted
50 Hz VERSION													
GA 5	7.5	75	109	15.0	54.0	31.7	5.5	75	60	257	317	300	360
	8.5	8.5	123	13.2	475	279	5.5	75	60	257	317	300	360
	10	10	145	11.7	42.1	24.7	5.5	75	60	257	317	300	360
	13	13	189	8.4	30.2	17.7	5.5	75	60	257	317	300	360
GA 7	7.5	75	109	21.0	75.6	44.3	7.5	10	61	270	330	315	375
	8.5	8.5	123	21.8	78.5	46.0	7.5	10	61	270	330	315	375
	10	10	145	17.2	70.6	36.3	7.5	10	61	270	330	315	375
	13	13	189	14.2	51.1	30.0	7.5	10	61	270	330	315	375
GA 11	7.5	75	109	30.7	110.5	64.8	11	15	62	293	353	343	403
	8.5	8.5	123	28.3	101.9	59.7	11	15	62	293	353	343	403
	10	10	145	26.0	93.6	54.9	11	15	62	293	353	343	403
	13	13	189	22.0	79.2	46.5	11	15	62	293	353	343	403

COMPRESSOR TYPE		Max. Working pressure WorkPlace		Capacity FAD* min-max			Installed motor power		Noise level**	Weight (kg)			
										WorkPlace		WorkPlace Full Feature	
		bar(e)	psig	l/s	m³/h	cfm	kW	hp		dB(A)	Floor-mounted	Tank-mounted	Floor-mounted
60 Hz VERSION													
GA 5	100	7.4	107	15.0	54.0	31.7	5.5	75	60	257	317	300	360
	125	9.1	132	13.2	475	279	5.5	75	60	257	317	300	360
	150	10.8	157	11.7	42.1	24.7	5.5	75	60	257	317	300	360
	175	12.5	181	8.4	30.2	17.7	5.5	75	60	257	317	300	360
GA 7	100	7.4	107	21.0	75.6	44.3	7.5	10	61	270	330	315	375
	125	9.1	132	21.8	78.5	46.0	7.5	10	61	270	330	315	375
	150	10.8	157	17.2	70.6	36.3	7.5	10	61	270	330	315	375
	175	12.5	181	14.2	51.1	30.0	7.5	10	61	270	330	315	375
GA 11	100	7.4	107	30.4	109.4	64.1	11	15	62	293	353	343	403
	125	9.1	132	27.0	97.2	57.0	11	15	62	293	353	343	403
	150	10.8	157	24.9	89.6	52.5	11	15	62	293	353	343	403
	175	12.5	181	22.0	79.2	46.4	11	15	62	293	353	343	403

\* Unit performance measured according to ISO 1217, Ed. 4, Annex C-2009.  
\*\* Mean noise level measured at a distance of 1 m according to ISO 2151; tolerance 3 dB(A).

Reference conditions:  
- Absolute inlet pressure 1 bar (14.5 psi).  
- Intake air temperature 20°C, 68°F

FAD is measured at the following working pressures:  
- 7.5 bar versions at 7 bar(e).  
- 8.5 bar versions at 8 bar(e).  
- 10 bar versions at 9.5 bar(e).  
- 13 bar versions at 12.5 bar(e).

GA 5-7-11 pack (floor-mounted)

GA 5-7-11 pack (tank-mounted)



Floor-mounted



Tank-mounted